www.kayakzebec.com Tel: 0818966017 Line ID: 66818966017 E-mail: ifo@gr.co.th



เครื่องยนต์ติดท้ายเรือ ซูซูกิ 6 แรงม้า แบบ 4 จังหวะ

Item specifications

item specifications	
Maximum output	6 HP
Number of cylinders	1
Engine type	4-stroke OHV 2-Valve
Starting system	Manual
Steering	Tiller
Engine mounting	Bushing type
Trim method	5 pin manual tilt
Piston displacement, cm ³	138
Piston displacement, in ³	8.4
Bore x Stroke, mm/mm	62 x 46
Bore x Stroke, in/in	2.44 x 1.81
Fuel delivery system	Carburetor
Alternator	12V 6A (optionally)**
Gear ratio	1.92:1
Gear shift	F-N-R
ropeller	3x7-1/2x7
Propeller rotation	Regular (Right-hand)
Propeller selection (pitch)*	6-7 "
Fuel tank capacity, L	1.5
Fuel tank capacity, US gal	0.39
Lubricating system	Circulating
Full trottle operating range	4750 - 5750
Ignition system	Digital CDI
NGK spark plug	CPR6EA-9 (from 2011y.)
Recommended transom height, mm	381
Recommended transom height, in	15
Oil pan capacity, ml	700
Oil pan capacity, fl oz	23.66
Lower unit gear oil capacity, ml	190
Lower unit gear oil capacity, fl oz	6.42
Dry Weight (including battery cable, not including propeller and engine oil), kg	25
Dry Weight (including battery cable, not including propeller and engine oil), lbs	55
Exhaust	Above prop exhaust
Drive protection	Rubber hub
Manufacturer	Suzuki